



(11) **EP 1 220 389 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
03.07.2002 Bulletin 2002/27

(51) Int Cl.7: **H01S 3/106**

(21) Application number: **01121409.5**

(22) Date of filing: **07.09.2001**

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
 Designated Extension States:
AL LT LV MK RO SI

• **Kallmann, Ulrich**
72070 Tübingen (DE)

(74) Representative: **Barth, Daniel**
c/o Agilent Technologies Deutschland GmbH,
Patentabteilung,
Herrenbergerstrasse 130
71034 Böblingen (DE)

(71) Applicant: **Agilent Technologies, Inc. (a Delaware corporation)**
Palo Alto, CA 94303 (US)

Remarks:
 Amended claims in accordance with Rule 86 (2) EPC.

(72) Inventors:
 • **Steffens, Wolf**
71083 Herrenberg (DE)

(54) **Optical path length variation for laser influencing**

(57) The present invention relates to a device for influencing an optical path length of a laser beam traveling a path (4), comprising: material (32, 42) in at least a part of the path (4), the material (32, 42) being voltage-, magnetism-, pressure-, humidity- and/or temperature-sensi-

tive, a changing element for changing the voltage, magnetism, pressure, humidity and/or temperature applied to the material (32, 42) to change a respective property of the material (32, 42) in a way which influences the optical path length of the path (4).




Fig. 1

BEST AVAILABLE COPY

EP 1 220 389 A1

Description

BACKGROUND OF THE INVENTION

[0001] The present invention relates to influencing a laser.

[0002] In the optical communication industry there is a need for testing optical components and amplifiers with lasers that can be tuned and influenced as required.

SUMMARY OF THE INVENTION

[0003] Therefore, it is an object of the invention to provide improved influencing of a laser. The object is solved by the independent claims.

[0004] According to the present invention, a material or device being sensitive in a characteristic property is applied in a path of a laser beam. The characteristic property can then be changed or varied for influencing the optical path length of the path.

[0005] The material or device (in the following - for the sake of simplicity - only referred to as 'material') can be any allowing to controllably vary its optical path length by applying a control property or signal thereto. Preferred embodiments may comprise pressure or stress induced variations of the optical path length, electro-optic modulators, optical piezo effect devices, liquid crystals (LC), or other adequate materials or devices.

[0006] The present invention thus allows influencing the optical path length of the laser beam traveling e.g. in a cavity. The invention provides easy and precise influencing for all kind of possibilities, e.g. tuning a laser beam, stabilizing a mode of a laser beam, stabilizing the wavelength of the laser beam or filtering a certain wavelength of a laser beam. Influencing a laser according to the present invention makes it possible to enhance the quality of the laser beam produced by the used laser source or laser cavity just by using known laser sources or laser cavities and incorporating the invention.

[0007] In a preferred embodiment of the invention, the material comprises a liquid crystal (LC). By using LCs, the present invention can be realized simple and cheap. The LC can be connected to a voltage source and can be influenced therewith easily. Especially the refractive index of such a LC can be influenced by different voltages and/or currents applied to the LC. By placing such LC in the path on which a laser beam is traveling, the optical path length of such a path can be manipulated easily.

[0008] A preferred embodiment of the present invention is claimed in a parallel application filed by the applicant (internal reference no. 20010438) at the same day as the present application, which application is incorporated herein by reference.

[0009] In a further preferred embodiment, the change of the optical path length is modulated, preferably in a sinusoidal way. This can be done by providing a (e.g. sinusoidally) modulated electrical control signal for the

LC that produces a (sinusoidal) optical path length variation. This leads to a frequency modulated output laser light with sidebands located at the carrier modulation frequencies and their higher harmonics if such LC is provided for tuning a laser.

[0010] For tuning a laser according to the invention, it is further preferred to change the optical path length to stabilize a mode of the laser beam within a small wavelength range. This range can be of the order of one mode spacing. In this embodiment, it is possible by a change of the optical path length to shift the lasing mode to the desired wavelength. This can also be done applying an external electrical signal to the LC as a control signal for the reflective index of the LC to tune the laser to the desired wavelength.

[0011] Another example of the inventive method provides a reduction of coherence of the laser light. This reduction can be used to avoid stimulated Brillouin Scattering or to avoid unwanted interference. A rapid change of the lasing mode wavelength by a change of the optical path length will produce laser light with these properties. An electrical control signal, which can be derived for example from random noise, can allow for the necessary optical path variations caused by the variation of the refractive index of the LC.

[0012] A preferred embodiment of the invention uses the material being a part of an etalon. This can be done for example by using a LC with highly reflective coatings on both sides. In such a LC, the highly reflective coated sides are the etalon mirrors. The tuning effect is again due to the optical path length change between the two highly reflective coated etalon mirrors. This device can be placed in the cavity of a laser source and its transmission wavelength can be controlled by the applied electrical signal to the LC. Furthermore, it is possible to reduce light at unwanted wavelengths (for example Source Spontaneous Emission (SSE) or longitudinal side modes), if the tuning mechanism of the tunable laser source in which the LC is placed and the etalon transmission wavelength are at least approximately synchronized with each other.

[0013] Another preferred embodiment of the invention uses the material in the path of the laser beam for providing a wave front correction of the laser beam. To achieve this goal the material can be built to provide a spatial variation, preferably a lateral variation of its properties, e.g. the refractive index. This can be achieved for example by multiple electrodes on each side of a LC layer. Individually switched these electrodes can produce a controllable electrical field, which varies over the lateral expansion of the respective LC layer. This variation can be utilized to correct the wave front errors or to create wave fronts with controllable and/or defined characteristics. A preferred embodiment for wave front variations is to emulate a 'lens' by laterally varying (i.e. perpendicular to the propagation direction of the laser beam) the refractive index effect.

[0014] The above-mentioned LC devices have the ad-

vantage that they can be placed anywhere within a cavity of a laser source. They can be inserted as a transmissive device, placed anywhere in the beam path. Preferably, they are slightly tilted with respect to the incoming beam to avoid any unwanted multi mirror effects due to none perfect antireflection coatings of the respective LC. However, a LC can also be used a reflective device. For such a reflective device one side of the LC device is highly reflective coated and acts as a cavity mirror. However, it is clear that the body of the LC is still in the path of the laser beam. Therefore, the body of the LC is still a transmissive device. Moreover, the other side of such LC device can still be antireflective coated to allow for maximum transmission into the body of the LC.

[0015] Other preferred embodiments are shown by the dependent claims.

[0016] It is clear that the invention can be partly embodied or supported by one or more suitable software programs, which can be stored on or otherwise provided by any kind of data carrier, and which might be executed in or by any suitable data processing unit.

BRIEF DESCRIPTION OF THE DRAWINGS

[0017] Other objects and many of the attendant advantages of the present invention will be readily appreciated and become better understood by reference to the following detailed description when considering in connection with the accompanied drawings. The components in the drawings are not necessarily to scale, emphasis instead being placed upon clearly illustrating the principles of the present invention. Features that are substantially or functionally equal or similar will be referred to with the same reference sign(s).

[0018] Fig. 1-4 show different embodiments of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

[0019] Referring now in greater detail to the drawings, Fig. 1 shows a schematic view of a first embodiment 1 of the apparatus of the present invention. The apparatus 1 of Fig. 1 comprises an external cavity 2, in which laser light provided by an active medium (not shown), e.g. a laser diode, can resonate to provide a laser beam 4. The beam 4 travels in the cavity 2 along a path between a cavity end element 6 and a tuning element 8 of the external cavity 2. The cavity end element 6 and the tuning element 8 both (providing a high reflective mirror) providing the cavity mirrors.

[0020] The apparatus 1 further comprises a dispersion element 10 introduced in the path of the beam 4 for selecting at least one, preferably a longitudinal, mode of the laser. The dispersion element 10 comprises a grating (not shown).

[0021] The tuning element 8 can be rotated by an actuator (not shown) about a pivot axis (not shown) to tune

the laser. The pivot axis is theoretically defined by the intersection of the surface plane of the cavity end element 6, the surface plane of the dispersion element 10 and the surface plane of the tuning element 8.

[0022] It is clear that the positioning of the elements 6, 8, 10 according to Fig. 1 is only schematic and not the ideal case of the positioning of the elements 6, 8, 10. The elements 6, 8, 10 however can be positioned in another way, i.e. in other angles or positions as shown in Fig. 1.

[0023] In the path 4 of the laser beam there is introduced additional material 32. The additional material 32 serves to change the optical length of the path 4 to at least partly compensate a shift between the real position of its rotation axis and the theoretically defined position (be aware that Fig. 1 is only a schematic illustration not to scale, therefore the axis is not shown). For further details about the predetermined path, reference is made to the parallel application mentioned above. In Fig. 1 are shown two collimators 34 and 36 to provide collimated laser light within the laser cavity (collimator 34) and to collimate the laser light 38 leaving the cavity end element 6 (collimator 36). The additional material 32 is explained in further detail with respect to Fig. 2.

[0024] An example of a refractive index changing material is shown in Fig 2. The additional material 32 is a so-called nematic LC (liquid crystal) retarder that provides phase shifts up to several π . A phase shift of one π corresponds to 1 mode spacing in cavity 2 with liquid crystal molecules 40. The liquid crystal molecules 40 are confined by two electrodes, here indium tin oxide (ITO) layers 46. The ITO layers 46 are contacted by wires 44 to receive a potential V. Part a) of Fig. 2 shows a situation with $V = 0$. In this case, the liquid crystal molecules 40 are aligned parallel to each other. This alignment is induced by layers 42 located on layers 46. Layers 42 and 46 are supported by glass substrate layers 48. All layers 42, 46 and 48 are transparent for the laser light of light beam 4. However, liquid crystal molecules 40 in the additional material 32 provide phase retardation to the laser light of light beam 4. This phase retardation is maximum with $V = 0$ as shown in part a) of Fig. 2.

[0025] When V is at its maximum the phase retardation is at its minimum as shown in part b) of Fig. 2. In this case, the liquid crystal molecules 40 are only partly aligned to each other.

[0026] Additional material 32 does not change the state of polarization of light beam 4 as indicated by arrows 50 in Fig. 1.

[0027] Fig. 3 shows a second embodiment 41 of the present invention. The general setup of embodiment 41 is similar to embodiment 1 of Fig. 1. However, in the path 4 of the laser beam there is introduced an etalon 42. The etalon 42 is built up by a LC 32 according to Fig. 2. The etalon 42 is slightly tilted with respect to the incoming beam 6 to avoid any unwanted multi mirror effects due to non perfect anti reflection coatings of the LC 32. However, the LC 32 is modified by two highly reflective coat-

ings 47 placed on the inner surfaces of the ITO layers 46. Thereby, an etalon 42 is created which can be manipulated by the same electrical signal applied to etalon 42 of Fig. 2. However, by changing the voltage applied to etalon 42 the transmission wavelength of etalon 42 can be manipulated, preferably synchronized with the tuning mechanism of the tuning element 8 to reduce light of unwanted wavelength, for example SSE or longitudinal side modes.

[0028] Fig. 4 shows a fourth embodiment 60 of the present invention. In this embodiment, the LC 32 serves also as a tuning element 8. To serve as the tuning element 8 only one ITO layer is coated by a highly reflective coating 47.

Claims

1. A method of influencing an optical path length of a laser beam (2) traveling a path (4), comprising the steps of:
 - providing a material (32, 42) in at least a part of the path (4), the material (32, 42) being sensitive in a characteristic property, and
 - changing the characteristic property of the material (32, 42) in a way which influences the optical path length of the path (4).
2. The method of claim 1, wherein the characteristic property is at least one of thickness, optical path length, or refractive index of the material (32, 42).
3. The method of the claims 1 or 2, wherein the characteristic property of the material is sensitive to at least one of voltage, magnetism, pressure, humidity, or temperature.
4. The method of any one of the claims 1 - 3, further comprising the step of:
 - additionally or alternatively changing the quantity of the introduced material (32, 42) in the path (4) to influence the optical path length of the path (4).
5. The method of any one of the claims 1-4, further comprising the step of:
 - modulating the change of the optical path length of the path (4), preferably using a modulation on a sinusoidal bases.
6. The method of any one of the claims 1-5, further comprising the step of:
 - varying the optical path length in a function of the spatial, preferably lateral, position in the laser beam.
7. The method of any one of the claims 1-6, further comprising the step of:
 - varying the characteristic property of the material spatially, preferably laterally, depending on the position in the laser beam.
8. A method of tuning a laser, comprising the steps of:
 - providing a laser beam (4) to an external cavity (2), the laser beam (4) traveling through material (32, 42) along a path (4) between a cavity and element (6) and a tuning element (8), the path (4) having an optical path length,
 - selecting a least one mode of the laser by introducing a dispersion element (10) in the path (4) of the laser, and
 - changing the optical path length of the path (4) by the method of any one of the claims 1-7 to stabilize a mode of the laser.
9. The method of claim 8, further comprising the steps of:
 - measuring the real wavelength,
 - comparing the real wavelength with the desired wavelength, and
 - generating a control signal depending on the deviation for controlling the amount of change necessary to at least partly compensate any deviation of a real wavelength from a desired wavelength.
10. The method of any one of the claims 8 or 9, further comprising the steps of:
 - performing the change of the optical path length rapidly, preferably by deriving a control signal for the change from random noise to reduce the coherence of the laser.
11. The method of any one of the claims 8 - 10, further comprising the step of:
 - synchronizing tuning of the laser with a transmission wavelength of the etalon (42).
12. A software program or product, preferably stored on a data carrier, for executing the method of any one of the claims 1 to 11 when run on a data processing system such as a computer.

13. A device for influencing an optical path length of a laser beam traveling a path (4), comprising:

a material (32, 42) in at least a part of the path (4), the material (32, 42) being sensitive in a characteristic property, 5

a changing element for changing the characteristic property of the material (32, 42) in a way which influences the optical path length of the path (4). 10

14. The device of claim 13, wherein the characteristic property is at least one of thickness or refractive index of the material (32, 42). 15

15. The device of the claims 13 or 14, wherein the characteristic property of the material is sensitive to at least one of voltage, magnetism, pressure, humidity, or temperature. 20

16. The device of any one of the claims 13 - 15, wherein the material (32, 42) provides a spatial, preferably a lateral, variation in its characteristic property. 25

17. The device of any one of the claims 13 - 16, wherein the material (32, 42) comprises a liquid crystal (32).

18. The device of any one of the claims 13 - 17, wherein the material (32, 42) is at least a part of an etalon (42). 30

19. An apparatus for tuning a laser, comprising:

an external cavity (2) for receiving a laser beam (4), the laser beam (4) traveling through material along a path (4) between a cavity end element (6) and a tuning element (8), the path (4) having an optical path length, 35

a dispersion element (10) introduced in the path (4) of the laser for selecting at least one mode of the laser, 40

a changing element for changing the optical path length of the path (4) comprising the device of any one of the claims 13 - 18. 45

50

55




Fig. 1




Fig. 2




Fig. 3




Fig. 4



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 12 1409

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 5 029 174 A (ANDERSON MARK W ET AL) 2 July 1991 (1991-07-02) * column 5, line 11 - column 6, line 13 * * column 8, line 50 - column 10, line 42; figure 5 *	1-4, 13-15	H01S3/106
X	US 4 937 833 A (KABACOFF LAWRENCE T) 26 June 1990 (1990-06-26) * column 4, line 26 - column 7, line 5; figure 7 *	1-3, 13-15	
X	US 4 803 692 A (MATSUMURA HIROYOSHI ET AL) 7 February 1989 (1989-02-07) * abstract * * column 2, line 46-68; figure 1 *	1-3, 13-15	
X	PATENT ABSTRACTS OF JAPAN vol. 012, no. 153 (E-607), 11 May 1988 (1988-05-11) -& JP 62 268172 A (YOKOGAWA ELECTRIC CORP), 20 November 1987 (1987-11-20) * abstract *	1-3,5, 13-15	
X	PATENT ABSTRACTS OF JAPAN vol. 1995, no. 04, 31 May 1995 (1995-05-31) -& JP 07 015062 A (NIPPON TELEGR & TELEPH CORP), 17 January 1995 (1995-01-17) * abstract *	1-3, 13-15, 17,18	TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			H01S G02F
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 6 March 2002	Examiner Gnugesser, H
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 03.82 (P04C01)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 12 1409

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	KOUROGI M ET AL: "LIMIT OF OPTICAL-FREQUENCY COMB GENERATION DUE TO MATERIAL DISPERSION" IEEE JOURNAL OF QUANTUM ELECTRONICS, IEEE INC. NEW YORK, US, vol. 31, no. 12, 1 December 1995 (1995-12-01), pages 2120-2125, XP000541555 ISSN: 0018-9197 * chapters II & III on pp. 2120 - 2122 * * figures 1 & 3 *	1-3,5, 13-15	
X	US 5 889 798 A (MOLVA ENGIN ET AL) 30 March 1999 (1999-03-30) * abstract * * column 7, line 30-38; figure 10 *	1-3, 13-15	
X	PATENT ABSTRACTS OF JAPAN vol. 016, no. 491 (P-1434), 12 October 1992 (1992-10-12) -& JP 04 177226 A (ASAHI GLASS CO LTD), 24 June 1992 (1992-06-24) * abstract *	1-3, 13-15	
X	DE 42 12 779 A (ZEISS CARL FA) 21 October 1993 (1993-10-21) * column 1, line 46-56 * * column 2, line 47-63 * * column 3, line 9 - column 5, line 15; figure 1 *	1-3,6,7, 13-17	
X	EP 0 852 415 A (UNIV MINNESOTA) 8 July 1998 (1998-07-08) * page 14, line 33 - page 14, line 45 * * page 17, line 7 - page 17, line 20; figure 4 *	1-3,6,7, 13-16	
		-/--	
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 6 March 2002	Examiner Gnugesser, H
CATEGORY OF CITED DOCUMENTS X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background O: non-written disclosure P: intermediate document		T: theory or principle underlying the invention E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons &: member of the same patent family, corresponding document	

EPO FORM 1503 03.92 (P04C01)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

EP 01 12 1409

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 5 283 796 A (FINK DAVID) 1 February 1994 (1994-02-01) * column 7, line 20-37; figure 10 *	1,2,5, 13,14	
X	EP 0 329 328 A (GEN ELECTRIC CO PLC) 23 August 1989 (1989-08-23) * column 4, line 5-36; figure 4 *	12	
X	US 5 097 476 A (THIESSEN RAINER) 17 March 1992 (1992-03-17) * column 5, line 38-51; figure 5 *	1-3, 13-15	
X	LASCHEK M ET AL: "Electro-optical frequency modulation of an external-cavity diode laser" OPTICS COMMUNICATIONS, NORTH-HOLLAND PUBLISHING CO. AMSTERDAM, NL, vol. 153, no. 1-3, 15 July 1998 (1998-07-15), pages 59-62, XP004146329 ISSN: 0030-4018 * chapters 1 & 2 * * figure 1 * * abstract *	1-3,5,8, 13-15,19	
X	EP 0 687 045 A (ANRITSU CORP) 13 December 1995 (1995-12-13) * column 10, line 1-52 * * column 20, line 6-45; figure 15 *	8,19	
Y	-/--	12	
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 6 March 2002	Examiner Gnugesser, H
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03-82 (P4-051)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 12 1409

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
Y	BINKS D J ET AL: "FREQUENCY LOCKING OF A PULSED SINGLE-LONGITUDINAL-MODE LASER IN A COUPLED-CAVITY RESONATOR" APPLIED OPTICS, OPTICAL SOCIETY OF AMERICA, WASHINGTON, US, vol. 36, no. 36, 20 December 1997 (1997-12-20), pages 9371-9377, XP000737203 ISSN: 0003-6935 * chapter "cavity design" * * figure 1 * * abstract *	12	
Y	PATENT ABSTRACTS OF JAPAN vol. 013, no. 429 (E-823), 25 September 1989 (1989-09-25) & JP 01 160072 A (KOMATSU LTD), 22 June 1989 (1989-06-22) * abstract *	8,9	
Y	EP 0 426 102 A (MITSUI PETROCHEMICAL IND) 8 May 1991 (1991-05-08) * column 5, line 45 - column 7, line 47; figure 4 *	8,9	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
Place of search MUNICH		Date of completion of the search 6 March 2002	Examiner Gnugesser, H
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 12 1409

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on.
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

06-03-2002

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5029174	A	02-07-1991	NONE	
US 4937833	A	26-06-1990	NONE	
US 4803692	A	07-02-1989	JP 62054991 A DE 3685466 D1 EP 0213965 A2	10-03-1987 02-07-1992 11-03-1987
JP 62268172	A	20-11-1987	NONE	
JP 07015062	A	17-01-1995	NONE	
US 5889798	A	30-03-1999	FR 2729797 A1 DE 69600692 D1 DE 69600692 T2 EP 0806065 A1 WO 9623335 A1 JP 11500577 T	26-07-1996 29-10-1998 22-04-1999 12-11-1997 01-08-1996 12-01-1999
JP 04177226	A	24-06-1992	NONE	
DE 4212779	A	21-10-1993	DE 4212779 A1	21-10-1993
EP 0852415	A	08-07-1998	US 5454004 A US 5627847 A EP 0852415 A2 AU 2636395 A EP 0758495 A1 JP 9512959 T WO 9531024 A2 US 5592505 A US 5745511 A	26-09-1995 06-05-1997 08-07-1998 29-11-1995 19-02-1997 22-12-1997 16-11-1995 07-01-1997 28-04-1998
US 5283796	A	01-02-1994	NONE	
EP 0329328	A	23-08-1989	GB 2215074 A EP 0329328 A2 US 4945539 A	13-09-1989 23-08-1989 31-07-1990
US 5097476	A	17-03-1992	DE 3917388 C1 DE 3943470 A1 DE 3943469 A1 EP 0402691 A1	29-11-1990 13-12-1990 21-02-1991 19-12-1990
EP 0687045	A	13-12-1995	JP 7335965 A JP 8018167 A	22-12-1995 19-01-1996

EPO FORM P0659

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 12 1409

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

06-03-2002

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
EP 0687045	A		DE	69514042 D1	27-01-2000
			DE	69514042 T2	09-08-2001
			EP	0687045 A2	13-12-1995
			US	5579327 A	26-11-1996

JP 01160072	A	22-06-1989	JP	2631482 B2	16-07-1997

EP 0426102	A	08-05-1991	JP	3142981 A	18-06-1991
			JP	3142982 A	18-06-1991
			CA	2028803 A1	01-05-1991
			EP	0426102 A2	08-05-1991
			US	5214659 A	25-05-1993

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record.

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.